

# SAFETY DATA SHEET

Industrial / Professional Use  
Only

## 1. PRODUCT AND COMPANY IDENTIFICATION

**RECOMMENDED USE:** Isocyanate-terminated Prepolymer

**PRODUCT CODE:** Mainstay 711 Sprayable Flexible Joint & Manhole Chimney Seal Part A

### MANUFACTURER

Madewell Products Corporation  
7561 Industrial Ct  
Alpharetta, GA 30004  
Office: (770) 475-8199  
Fax: (770) 475-8167  
Website: www.madewell.net  
Email: sales@madewell.net

### 24 HR. EMERGENCY TELEPHONE NUMBERS

**PERS 800-633-8253**

EMERGENCY TELEPHONE NUMBER: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals.

## 2. HAZARDS IDENTIFICATION

### GHS CLASSIFICATIONS

Acute Toxicity (Inhalation), Category 4  
Target Organ Toxicity (Single exposure), Category 3  
Target Organ Toxicity (Repeated exposure), Category 1  
Respiratory Sensitization, Category 1  
Skin Irritation, Category 2  
Skin Sensitization, Category 2  
Eye Irritation, Category 2

### GHS LABEL

**According to Regulation 20 12 OSHA Hazard Communications Standard: 29 CFR Part 1910.1200**



Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** DANGER

### HAZARD STATEMENTS

H315: Causes skin irritation.  
H372:: Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.  
H320: Causes eye irritation. H332: Harmful if inhaled.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317: May cause an allergic skin reaction.  
H335: May cause respiratory irritation.  
H372:: Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

### PRECAUTIONARY

#### STATEMENTS Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P264: Wash skin and face thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area.  
P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P285: In case of inadequate ventilation wear respiratory protection.

#### Response:

P314: Get medical advice/attention if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water. P342: If experiencing respiratory symptoms:.

P337+P313: If eye irritation persists: Get medical advice/

attention. P332+P313: If skin irritation occurs: Get medical advice/attention. P363: Wash contaminated clothing before reuse.

#### Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

#### Disposal:

P501: Dispose of contents/container in accordance with existing federal, state and local environmental control laws.

### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Clear straw color liquid.

**IMMEDIATE CONCERNS:** CAUTION: Contains DIPHENYLMETHANE DIISOCYANATE (CAS no. 101-68-8). Inhalation of MDI mists or vapors may cause respiratory irritation, breathlessness, chest discomfort and reduced pulmonary function. Overexposure well above the PEL may result in bronchitis, bronchial spasms and pulmonary edema. Long-term exposure to isocyanates has been reported to cause lung damage, including reduced lung function which may be permanent. Acute or chronic overexposure to isocyanates may cause sensitization in some individuals, resulting in allergic respiratory reactions including wheezing, shortness of breath and difficulty breathing.

### POTENTIAL HEALTH EFFECTS

**EYES:** May cause significant irritation to the eyes.

**SKIN:** Allergic reaction and significant irritation to the skin is possible. **INGESTION:** May cause significant irritation to the digestive tract. **INHALATION:** Irritating to the nose, throat and respiratory tract.

**MEDICAL CONDITIONS AGGRAVATED:** Individuals who are sensitized to isocyanates and those with asthma, respiratory disorder, skin allergies, and eczema.

**SENSITIZATION:** Possible sensitizer by inhalation and skin contact.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyurethane Prepolymer	45 - 55	Trade Secret
Methylenediphenyl Diisocyanate	25 - 35	26447-40-5
Methylene Bisphenyl Isocyanate	15 - 25	101-68-8

**COMMENTS:** Criteria for listing components in this SDS are as follows: Carcinogens are listed at 0.1% or greater; hazardous components according to regulation 2012 OSHA Hazard Communication Standard: 29 CFR 1910.1200 are listed at 1.0% or greater; non-hazardous components are not listed. This is not intended to be the complete compositional disclosure. If a "Trade Secret" "(TS)" is claimed in accordance to paragraph (i) of 1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**EYES:** Immediately flush with plenty of water for two minutes. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Have eyes examined and tested by medical personnel.

**SKIN:** Remove contaminated clothing and immediately wash affected skin area with plenty of soap and water. Seek medical attention. Either discard or wash contaminated clothing and shoes before reuse.

**INGESTION:** Make sure victim is conscious and alert. If so, give 2-3 glasses of water to dilute. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Immediate medical attention is required. Do not leave victim unattended as spontaneous vomiting may occur. Lay victim on side with head lower than waist to prevent aspiration of swallowed product. If victim is conscious and vomiting occurs, give water to further dilute the chemical.

**INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Seek medical attention if cough or other symptoms develop.

#### **SIGNS AND SYMPTOMS OF OVEREXPOSURE**

**ACUTE EFFECTS:** Isocyanates have also been reported to cause hypersensitivity pneumonitis, which is characterized by flu-like symptoms, the onset of which may be delayed. Gastrointestinal symptoms include nausea, vomiting and abdominal pain.

**CHRONIC EFFECTS:** Results from a lifetime study in rats indicate that MDI aerosol was carcinogenic at 6 mg/m<sup>3</sup>, the highest dose tested. This is well above the recommended TLV of 5 ppb (0.05 mg/m<sup>3</sup>). Only irritation was noted at the lower concentration of 0.2 and 1 mg/m<sup>3</sup>. No birth defects or teratogenic effects were reported in a teratology study with rats exposed to 1, 4, and 12 mg/m<sup>3</sup> polymeric MDI or 6 hr/day on days 6-15 of gestation. Embryotoxicity and fetotoxicity was reported at the top dose in the presence of maternal toxicity.

As a result of the previous repeated overexposures or single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to later exposure to isocyanate at levels well below the PEL/TLV. These symptoms, which include chest tightness, wheezing, cough, shortness of breath, or asthmatic attack, could be immediate or delayed up to several hours after exposure. This increased lung sensitivity can persist for weeks and in severe cases for several years.

### **5. FIRE FIGHTING MEASURES**

**FLAMMABLE CLASS:** Not

Applicable

**EXTINGUISHING MEDIA:** Dry Chemical, Foam, or Carbon Dioxide. Water is not recommended due to reaction.

**FIRE FIGHTING PROCEDURES:** Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Fire fighting personnel are required to use respiratory and eye protection. Full fire protective equipment (Bunker Gear) and self contained breathing apparatus (SCBA) is recommended to be used for all indoor fires and any significant outdoor fires. SCBA may not be required for small outdoor fires that may easily be extinguished with a portable fire extinguisher.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of Nitrogen, Oxides of Carbon.

### **6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as diatomaceous earth, sawdust, vermiculite, or any appropriate readily available material and sweep or shovel absorbed material into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wash the contaminated area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

Wear the appropriate personal protective equipment designated in Section 8, remove the leaking container to a containment area and place into an appropriate container to prevent any further spill.

**LARGE SPILL:** Construct temporary dikes of dirt or sand to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as diatomaceous earth, sawdust, vermiculite, or any appropriate readily available material and sweep or shovel adsorbed material into closed containers for disposal. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

Wear the appropriate personal protective equipment designated in Section 8, close or cap leaking valves and/or block or plug hole in leaking container. Remove the leaking containers to a containment area and place into an appropriate container to prevent any further spill.

Contain material as described above and call the local fire, police, or appropriate emergency response provider for immediate emergency assistance.

**ENVIRONMENTAL PRECAUTIONS**

**WATER SPILL:** Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of material into sources of water.

**GENERAL PROCEDURES:** Absorb spill with an emergency spill kit, diatomaceous earth, saw dust or equivalent inert material. Shovel up and dispose of at an appropriate waste disposal facility following applicable laws and regulations.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Store product in original containers. Store container in a secure cool, dry, well ventilated area at 55-85 deg. F. Opened containers should be blanketed with nitrogen gas at atmospheric pressure to avoid reaction with moisture. Contamination with moisture or "basic" compounds can cause dangerous pressure buildup in closed containers.

**HANDLING :** Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Avoid breathing in vapors, mists, and aerosols. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

**STORAGE:** Store and warehouse product in an appropriate area or facility. Segregate like materials together to avoid negative chemical reactions. Protect materials from excessive exposure to heat. Observe proper storage conditions and temperatures.

**STORAGE TEMPERATURE:** (55°F) Minimum to (85°F) Maximum

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE GUIDELINES****OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)**

Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m <sup>3</sup>
Methylene Bisphenyl Isocyanate	OSHA PEL	TWA	.02	.2
		STEL	.02	
	ACGIH TLV	TWA	.005	
		Supplier OEL	TWA	[1]
	STEL		[1]	[1]

**OSHA TABLE COMMENTS:**

1. Not Established

**ENGINEERING CONTROLS:** Proper industrial hygiene practices are required for workers and should be achieved through engineering controls including ventilation with a high turn over rate whenever feasible. When such controls are not available or not feasible to achieve full protection, respirators for workers (and others in the area) and other personal protective equipment is mandated. Exhaust air may need to be scrubbed (cleaned) or filtered to reduce environmental contamination and odors.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) and a face shield.

**SKIN:** Wear impervious compatible chemical resistant protective clothing such as neoprene or butyl rubber gloves, aprons, boots or Tyvek coveralls, as appropriate to prevent contact with skin.

**RESPIRATORY:** For respirator selection and training, seek professional advice. Whenever workplace conditions require a use of a respirator, follow a respiratory protection program that meets OSHA (29CFR 1910.134), MSHA (30 CFR Parts 56 & 57) and ANSI (Z88.2) requirements. Wear an OSHA/NIOSH approved respirator selected on its suitability to provide adequate worker protection for respirable particulates based on airborne workplace concentrations and duration of exposure arising from intended end use.

**WORK HYGIENIC PRACTICES:** Always follow "Good personal hygiene practices" when working with this material.

**COMMENTS:** Always practice "good personal hygiene" during and after use of this materials, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. DO NOT eat, drink, or smoke in work areas that contain hazardous chemicals.

**9. PHYSICAL AND CHEMICAL****PROPERTIES PHYSICAL STATE:** Liquid**ODOR:** Faint aromatic odor.**ODOR THRESHOLD:** No data available**COLOR:** Clear to pale yellow**pH:** No data available**FLASHPOINT AND METHOD:** > (200°F) Pensky-Martens CC**FLAMMABLE LIMITS:** No data available**VAPOR PRESSURE:** < 0.001 mmHg at25°C **VAPOR DENSITY:** No data available**BOILING POINT:** 208°C (406.4°F)**FREEZING POINT:** < 0°C (32°F)**SOLUBILITY IN WATER:** Insoluble in water, reacts with evolution of CO<sub>2</sub>**EVAPORATION RATE:** No data available**SPECIFIC GRAVITY:** 1.12 g/cm<sup>3</sup> at 25°C (77°F) **VISCOSITY:** No data available**(VOC):** 0 g/l**Notes:** VOC listed on the SDS is for this component only. Mixed VOC for the combined product may have a different value. Consult the manufacturer or product data sheet for final mixed product VOC value.**10. STABILITY AND REACTIVITY****HAZARDOUS POLYMERIZATION:** May occur if material is in contact with moisture.**STABILITY:** This material (product) is stable under normal ambient conditions of temperature and pressure. Follow recommendations for proper storage and use.**CONDITIONS TO AVOID:** Avoid high temperatures, sources of ignition, and moisture.**INCOMPATIBLE MATERIALS:** Water, strong bases, strong acids, strong oxidizing agents, alcohols, and amines.**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Methylene Bisphenyl Isocyanate	31600 mg/kg	> 5000 mg/kg	10 to 20 mg/l

**DERMAL LD<sub>50</sub>:** > 9400 mg/kg (rabbit)**ORAL LD<sub>50</sub>:** > 2000 mg/kg (rabbit)**INHALATION LC<sub>50</sub>:** > .49 mg/l , 490, (4 HR rat) **SKIN****CORROSION/IRRITATION:** Slightly irritating **SERIOUS****EYE DAMAGE/IRRITATION:** Slightly Irritating**GERM CELL MUTAGENICITY:** Product is a blend of material that has been shown to be Ames Negative (non mutogenic)**CARCINOGENICITY****IARC:** Not Listed by IARC.**NTP:** Not listed by NTP.**OSHA:** Not listed by OSHA.**GENERAL COMMENTS:** This product does contain substances considered by OSHA, NTP, IARC or ACGIH to be "probable" or "suspected" human carcinogens [Ethylbenzene (100-41-4)].**COMMENTS:** The chemical, physical, and toxicological properties have not been thoroughly investigated or tested to the best of our knowledge.**12. ECOLOGICAL INFORMATION**

**ENVIRONMENTAL DATA:** No environmental data has been established or is available for this product.

**GENERAL COMMENTS:** Avoid contaminating waterways.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** See the manufacturers instructions to mix together with the proper components of multi-component materials, and allow to harden. Dispose solids at an appropriate waste disposal facility according to current applicable laws and regulations.

**COMMENTS:** Refer to Section 6. Accidental Release Measures for additional information.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Other regulated substances, liquid, n.o.s. (contains Diphenylmethane Diisocyanate (MDI))

**PRIMARY HAZARD CLASS/DIVISION:** 9

**UN/NA NUMBER:** 3082

**PACKING GROUP:** III

**REPORTABLE QUANTITY (RQ) UNDER CERCLA:** 10549 kg

**OTHER SHIPPING INFORMATION:** When in individual containers of less than the Product RQ, this material ships as non-regulated.

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Regulated

#### VESSEL (IMO /IMDG)

**SHIPPING NAME:** Not Regulated

#### CANADA TRANSPORT OF DANGEROUS GOODS

**SHIPPING NAME:** Not Regulated

### 15. REGULATORY INFORMATION

#### UNITED STATES

##### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** Miscellaneous

**313 REPORTABLE INGREDIENTS:** 101-68-8 Diisocyanates

##### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

**CERCLA REGULATORY:** 101-68-8 Diisocyanates

##### TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS:** All ingredients in this mixture are listed with the TSCA Chemical Substance Inventory.

#### REGULATIONS

**STATE REGULATIONS:** The following product components are cited on certain state lists as mentioned. Non-listed components may be shown in the composition section of the MSDS.

Methylene bis(phenylisocyanate) (MDI) CAS# 101-68-8

New Jersey Environmental Hazardous Substances, New Jersey Workplace Hazardous Substances

Pennsylvania Environmental Hazardous Substances, Pennsylvania Hazardous Substances

#### CANADA

##### WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):



Poison


## 16. OTHER INFORMATION

Date Prepared: 03/14/2018

## HMIS RATING

HEALTH	<input type="checkbox"/>	<input type="checkbox"/>
FLAMMABILITY	<input type="checkbox"/>	<input type="checkbox"/>
PHYSICAL HAZARD	<input type="checkbox"/>	<input type="checkbox"/>
PERSONAL PROTECTION	G	

## NFPA CODES



**MANUFACTURER DISCLAIMER:** This SDS to the best of our knowledge conforms to the requirements of 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200, and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Responsibility for the product sold is subject to our standard terms and conditions, a copy of which is available upon request. This company warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, NO GUARANTY, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS, OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. Liability by this company for all claims, whether arising out of breach of warranty, negligence, strict liability, or otherwise, is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, the user should obtain detailed information on toxicity, together with the proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards. Toxicity and risk characteristics of chemical compounds and other products may differ when used with other materials or in a manufacturing or other process. Those risk characteristics should be determined by the user and made known to handlers, processors, and end users.

# SAFETY DATA SHEET

Industrial / Professional Use Only

Date Prepared: 08/09/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

**RECOMMENDED USE:** Amine Mixture

**PRODUCT CODE:** Mainstay 711 Sprayable Flexible Joint & Manhole Chimney Seal Part B

### MANUFACTURER

Madewell Products Corporation  
7561 Industrial Ct  
Alpharetta, GA 30004  
Office: (770) 475-8199  
Fax: (770) 475-8167  
Website: www.madewell.net  
Email: sales@madewell.net

### 24 HR. EMERGENCY TELEPHONE NUMBERS

**PERS 800-633-8253**

EMERGENCY TELEPHONE NUMBER: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals.

## 2. HAZARDS IDENTIFICATION

### GHS CLASSIFICATIONS

Acute Toxicity (Oral), Category 4  
Acute Toxicity (Dermal), Category 4  
Skin Corrosion, Category 1B  
Skin Irritation, Category 1B  
Eye Corrosion, Category 1  
Eye Irritation, Category 2A  
Aquatic Toxicity, Category 3  
Target Organ Toxicity (Repeated exposure), Category 2

### GHS LABEL

According to Regulation 20 12 OSHA Hazard Communications Standard: 29 CFR Part 1910.1200



Exclamation  
mark



Health  
hazard



Corrosion

**SIGNAL WORD:** WARNING

### HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.  
H302 + H312: Harmful if swallowed or in contact with skin.  
H312: Harmful in contact with skin.  
H373: May cause damage to organs through prolonged or repeated exposure.

### PRECAUTIONARY

#### STATEMENTS Prevention:

P273: Avoid release to the environment.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P270: Do not eat, drink or smoke when using this product. P264: Wash skin and face thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

#### Response:

P314: Get medical advice/attention if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P301+P312: IF SWALLOWED: Call a POISON CENTER/ doctor/...if you feel unwell.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P337+P313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

#### Storage:

P405: Store locked up.

#### Disposal:

P501: Dispose of contents/container in accordance with existing federal, state and local environmental control laws.

### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Amber Liquid

**IMMEDIATE CONCERNS:** USE WITH CAUTION! Corrosive to eyes, skin, and respiratory system. Severe irritant to eyes and skin. May cause sensitization to the respiratory system. May cause sensitization to the skin. Components of the product may have affect on the nervous system.

### POTENTIAL HEALTH EFFECTS

**EYES:** This product and its vapors may cause eye irritation, burns, or even blindness.

**SKIN:** Causes skin burns, irritation and possible allergic reaction.

**INGESTION:** Severe burns of the mouth and throat are possible if ingested, as well as a danger of perforation of the digestive tract.

**INHALATION:** Vapors may be irritating to the upper respiratory tract (including the nasal area) and eyes. Can cause severe eye, skin, and respiratory tract burns. May cause nose, throat, and lung irritation. Prolonged or repeated exposure to high concentrations may be harmful and cause adverse effects including labored breathing.

**MEDICAL CONDITIONS AGGRAVATED:** Eye disease, Skin disorders and Allergies. Adverse skin effects (such as rash, irritation or burns). Adverse eye effects (such as conjunctivitis or corneal damage). Asthma. Adverse respiratory effects (such as cough, tightness of chest or shortness of breath).

**TARGET ORGAN STATEMENT:** Eyes, Respiratory System, and Skin.

**SENSITIZATION:** Possible sensitizer by skin contact.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Diethylmethylbenzenediamine	10 - 25	68479-98-1

### 4. FIRST AID MEASURES

**EYES:** Immediately flush with plenty of water for two minutes. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Have eyes examined and tested by medical personnel.

**SKIN:** Remove contaminated clothing and immediately wash affected skin area with plenty of soap and water. Seek medical attention. Either discard or wash contaminated clothing and shoes before reuse.

**INGESTION:** Make sure victim is conscious and alert. If so, give 2-3 glasses of water to dilute. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Immediate medical attention is required. Do not leave victim unattended as spontaneous vomiting may occur. Lay victim on side with head lower than waist to prevent aspiration of swallowed product. If victim is conscious and vomiting occurs, give water to further dilute the chemical.

**INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Seek medical attention if cough or other symptoms develop.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**INHALATION:** Repeated and/or prolonged exposure to low concentrations of vapors may cause a "Sore Throat".

**ACUTE EFFECTS:** Sensitization, irritation and dermatitis.

**CHRONIC EFFECTS:** This product contains no listed carcinogens according to IARC, ACGIH, NTP, and/or OSHA in

concentrations of 0.1 percent or greater (unless identified under section 15 of this MSDS). Repeated or prolonged contact causes sensitization, asthma, and eczema. Prolonged contact may result in chemical burns and permanent damage.

**ADDITIONAL INFORMATION:** Seek medical advice and/or treatment. If breathing is irregular or stopped, administer artificial respiration and call 911.

## 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Not applicable

**GENERAL HAZARD:** Evacuate personnel upwind of a fire to avoid inhalation of irritating and/or harmful fumes and smoke.

**EXTINGUISHING MEDIA:** Dry Chemical, Foam, or Carbon Dioxide. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop spill or leak and to disperse vapors.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand, (AS/NZS 1715 and AS/NZS 1716 approved or equivalent) and full protective gear. Toxic vapors may evolve. Fight fires from a safe distance or protected areas. Use of large volumes of water may produce run-off that could be toxic to wildlife and/or pose a hazardous waste disposal issue. Water may not be effective for large fires.

**FIRE FIGHTING EQUIPMENT:** Fire fighting personnel are required to use respiratory and eye protection. Full fire protective equipment (Bunker Gear) and self contained breathing apparatus (SCBA) is recommended to be used for all indoor fires and any significant outdoor fires. SCBA may not be required for small outdoor fires that may easily be extinguished with a portable fire extinguisher.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic nitrogen oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as diatomaceous earth, sawdust, vermiculite, or any appropriate readily available material and sweep or shovel absorbed material into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wash the contaminated area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

Wear the appropriate personal protective equipment designated in Section 8, remove the leaking container to a containment area and place into an appropriate container to prevent any further spill.

**LARGE SPILL:** Construct temporary dikes of dirt or sand to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as diatomaceous earth, sawdust, vermiculite, or any appropriate readily available material and sweep or shovel adsorbed material into closed containers for disposal. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

Wear the appropriate personal protective equipment designated in Section 8, close or cap leaking valves and/or block or plug hole in leaking container. Remove the leaking containers to a containment area and place into an appropriate container to prevent any further spill.

Contain material as described above and call the local fire, police, or appropriate emergency response provider for immediate emergency assistance.

### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of material into sources of water.

**GENERAL PROCEDURES:** Absorb spill with an emergency spill kit, diatomaceous earth, saw dust or equivalent inert material. Shovel up and dispose of at an appropriate waste disposal facility following applicable laws and regulations.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Store product in original containers. Store in a cool, dry, well ventilated area.

**HANDLING :** Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and

prolonged skin exposure. Avoid breathing in vapors, mists, and aerosols. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

**STORAGE:** Store and warehouse product in an appropriate area or facility. Segregate like materials together to avoid negative chemical reactions. Protect materials from excessive exposure to heat. Observe proper storage conditions and temperatures.

**STORAGE TEMPERATURE:** (50°F) Minimum to (75°F) Maximum

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

#### OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)

Chemical Name	EXPOSURE LIMITS			
	Type	ppm	mg/m <sup>3</sup>	
Diethylmethybenzenediamine	Supplier OEL	TWA	0.02 ppm	0.13 mg/m <sup>3</sup>

**ENGINEERING CONTROLS:** Proper industrial hygiene practices are required for workers and should be achieved through engineering controls including ventilation with a high turn over rate whenever feasible. When such controls are not available or not feasible to achieve full protection, respirators for workers (and others in the area) and other personal protective equipment is mandated. Exhaust air may need to be scrubbed (cleaned) or filtered to reduce environmental contamination and odors.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety goggles or safety glasses with side shields when handling and mixing this material.

**SKIN:** Wear impervious compatible chemical resistant protective clothing such as neoprene or butyl rubber gloves, aprons, boots or Tyvek coveralls, as appropriate to prevent contact with skin.

**RESPIRATORY:** For respirator selection and training, seek professional advice. Whenever workplace conditions require a use of a respirator, follow a respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements. Wear an OSHA/NIOSH approved respirator selected on its suitability to provide adequate worker protection for the chemicals used and given working conditions including the level of airborne contamination and presence of sufficient oxygen.

**WORK HYGIENIC PRACTICES:** Always follow "Good personal hygiene practices" when working with this material.

**COMMENTS:** Always practice "good personal hygiene" during and after use of this materials, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. DO NOT eat, drink, or smoke in work areas that contain hazardous chemicals.

## 9. PHYSICAL AND CHEMICAL

**PROPERTIES PHYSICAL STATE:** Liquid

**ODOR:** Ammonia smell

**COLOR:** Black visous liquid

**pH:** 10 to 11

**PERCENT VOLATILE:** None

**FLASHPOINT AND METHOD:** > (230°F) Pensky-Martens CC

**FLAMMABLE LIMITS:** Does not support combustion

**AUTOIGNITION TEMPERATURE:** > 230°C

**VAPOR PRESSURE:** < 1 mbar

**VAPOR DENSITY:** Not

Available **BOILING POINT:** >

250° C **SOLUBILITY IN**

**WATER:** Slight

**EVAPORATION RATE:** Not Available

**SPECIFIC GRAVITY:** 1.014 g/cm<sup>3</sup> at 25°C (74°F)

**VISCOSITY #1:** 200 to 400 Centipoise

**(VOC):** 0 g/l Estimated

**Notes:** VOC listed on the SDS is for this component only. Mixed VOC for the combined product may have a different value. Consult the manufacturer or product data sheet for final mixed product VOC value.

## 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** None

**STABILITY:** This material (product) is stable under normal ambient conditions of temperature and pressure. Follow recommendations for proper storage and use.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Nitric Acid, Ammonia, Nitrogen oxides, Nitrogen oxide can react with water vapors to form corrosive nitric acid, Carbon monoxide, Carbon dioxide, Aldehydes.

**INCOMPATIBLE MATERIALS:** Reactive metals (e.g. sodium, calcium, zinc, etc.), Materials reactive with hydroxyl compounds, Organic acids (e.g. acetic acid, citric acid, etc.), Mineral acids, Sodium hypochlorite, Oxidizing agents, Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion, Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Diethylmethylbenzenediamine	472 mg/kg	> 2000 mg/kg	> 0.61 mg/l

**DERMAL LD<sub>50</sub>:** > 5000 mg/kg (rat)

**GERM CELL MUTAGENICITY:** Product is a blend of material that has been shown to be Ames Negative (non mutogenic)

### CARCINOGENICITY

**IARC:** Not Listed by IARC.

**NTP:** Not listed by NTP.

**OSHA:** Not listed by  
OSHA.

**GENERAL COMMENTS:** This product does not contain substances considered by OSHA, NTP, IARC or ACGIH to be "probable" or "suspected" human carcinogens.

**COMMENTS:** The chemical, physical, and toxicological properties have not been thoroughly investigated or tested to the best of our knowledge.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** No environmental data has been established or is available for this product.

**GENERAL COMMENTS:** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** See the manufacturers instructions to mix together with the proper components of multi-component materials, and allow to harden. Dispose solids at an appropriate waste disposal facility according to current applicable laws and regulations.

**COMMENTS:** Refer to Section 6. Accidental Release Measures for additional information.

## 14. TRANSPORT INFORMATION

**DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Not Regulated

## 15. REGULATORY INFORMATION

### UNITED STATES

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**FIRE:** No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

**CANADA**

**WHMIS HAZARD SYMBOL AND CLASSIFICATION**



Toxic

**DOMESTIC SUBSTANCE LIST (INVENTORY):** The components in this product are listed or exempt from the Canadian Domestic Substance List (DSL).


**16. OTHER INFORMATION**

**Date Prepared:** 08/09/2021

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<input type="checkbox"/>
<b>FLAMMABILITY</b>	<input type="checkbox"/>	<input type="checkbox"/>
<b>PHYSICAL HAZARD</b>	<input type="checkbox"/>	<input type="checkbox"/>
<b>PERSONAL PROTECTION</b>	<b>G</b>	

**NFPA CODES**



**MANUFACTURER DISCLAIMER:** This SDS to the best of our knowledge conforms to the requirements of 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200, and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Responsibility for the product sold is subject to our standard terms and conditions, a copy of which is available upon request. This company warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, **NO GUARANTY, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS, OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT.** Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. Liability by this company for all claims, whether arising out of breach of warranty, negligence, strict liability, or otherwise, is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, the user should obtain detailed information on toxicity, together with the proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards. Toxicity and risk characteristics of chemical compounds and other products may differ when used with other materials or in a manufacturing or other process. Those risk characteristics should be determined by the user and made known to handlers, processors, and end users.